

# FS-1010/1050

Design by F.A. Porsche. Speed and cost-efficiency by Kyocera Mita.

14 ppm Desktop Printers

► Print ► Copy ► Scan ► Fax



*Ecosys*®

 **KYOCERA**  
*mita*

## FS-1010/1050 PRINTERS

	<b>GENERAL</b>	<b>CPU</b>	<b>CONTROLLER</b>	<b>OPTIONS</b>
<b>Technology</b>	Kyocera Mita ECOSYS, Laser	<b>Memory</b>	PowerPC 405/200 MHz	<b>Printer memory</b>
<b>Type</b>	Desktop		Standard 16 MB + ECOMemory	1 slot (16, 32, 64, 128 MB DIMM) expansion
<b>Engine speed</b>	14 pages (A4) per minute		Max. 144 MB, 1 additional DIMM slot (16, 32, 64, 128 MB)	<b>CompactFlash* card</b>
<b>First print time</b>	12 seconds or less	<b>Emulations</b>	PCL6 incl. P.J.L., KPDL2 (PostScript2 compatible), Line Printer, IBM Proprinter X24E, Epson LQ-850, Diablo 630	1 slot (8 MB) forms, fonts, logos, macro storage
<b>Resolution</b>	Fast 1200 dpi resolution, up to 2400 dpi quality with KIR2 technology	<b>Controller language</b>	PRESCRIBE IIe	<b>Paper feed unit PF-17</b>
<b>Warm-up time</b>	15 seconds or less	<b>Fonts</b>	80 scalable fonts incl. International character set, 45 barcodes with automatic checksum generation (e.g. EAN 8 / EAN 13 / EAN 128) incl. two dimensional barcode (PDF-417)	<b>Paper cassette PC-42</b>
<b>Duty Cycle</b>	Max. 10,000 pages per month	<b>Standard interfaces</b>	<b>INTERFACE / NETWORK</b> Standard IEEE 1284, USB 2.0, optional interface port	250-sheet 60-105 g/m <sup>2</sup> for FS-1010 / FS-1050
<b>Power Consumption</b>	Printing: 265 W (FS-1010) Printing: 268 W (FS-1050) Stand-by: 13 W Sleeping: 5 W	<b>Multiple Interface Connection (MIC)</b>	MIC allows for simultaneous data transfer via up to three interfaces, with each interface having its own virtual printer.	<b>Paper cassette PC-40F</b>
<b>Noise</b>	Printing: 50 dB Stand-by: 28 dB	<b>Message display</b>	<b>USER INTERFACE</b> LCD display (FS-1050) Multiple language support	250-sheet 60-105 g/m <sup>2</sup> for PF-17
<b>Power source</b>	AC 220 ~ 240 V, 50/60 Hz	<b>Toner Kit TK-17</b>	<b>CONSUMABLES</b> Microfine Toner for 6,000 pages with 5% coverage.	<b>Optional interface/network</b>
<b>Dimensions (WxDxH)</b>	378 x 375 x 222 mm (FS-1010) 378 x 375 x 244 mm (FS-1050)			<b>Network card IB-21E</b>
<b>Weight</b>	Approx. 9.5 kg (FS-1010) Approx. 9.8 kg (FS-1050)			<b>Network card SB-140</b>
<b>Certification</b>	TUV-GS/CE These printers are produced according to the quality norm ISO 9001 and the environmental guidelines ISO 14001.			<b>Network card IB-10E</b>
<b>Paper capacity</b>	<b>PAPER HANDLING</b> 250 sheets universal cassette, 60-105 g/m <sup>2</sup> , A4, A5, B5, Letter, Custom (148 x 210 mm - 216 x 297 mm) 50 sheets multi-bypass, 60-163 g/m <sup>2</sup> A4, A5, B5, Letter, Legal, Custom (70 x 148 mm - 216 x 297 mm)			<b>Network card SB-60</b>
<b>Output capacity</b>	150-sheet face-down			<b>Network card SB-110FX</b>

ECOSYS technology is based on extremely durable components. The drum, developer and fuser of the FS-1010 and FS-1050 are designed for 100,000 pages. Due to the fact that toner is the only consumable required, ECOLaser Printers operate with the lowest cost per page in their class, and they are particularly environmental friendly. Thanks to their numerous system, paper options and modularity, all ECOLaser Printers can develop to meet further requirements.

#### PRESCRIBE IIe

With the Kyocera Mita page design and control language PRESCRIBE IIe, even complex graphics, logos and standard forms can be created independently of the system and saved in the printer. Consequently, integration into print files no longer applies. They are only accessed as required and therefore relieve the load on the network.

#### Typefaces and barcodes

The 80 scalable, high-quality fonts can be selected from all emulations. It is therefore also possible to integrate

old systems without any problems. A total of 45 integrated barcodes including hash totals are computed automatically by the printer and printed in the desired size, alignment and position.

#### API for individual solutions

The Application Programming Interface (API) is a highly efficient interface for the programming of individual print solutions - e.g. for the management of standard forms and documents. API is 100% compatible with applications by SAP and UNIX systems and therefore it allows the integration of popular output management systems.

#### KM-NET VIEWER

The KM-NET VIEWER enables complete monitoring and control of Kyocera Mita ECOLaser printers and multi-functional products from every computer. KM-NET VIEWER therefore offers ideal network administration as well as supporting the standardized protocol SNMP. The new gas gauge function monitors from your PC the toner

levels and paper quantity contributing to the total efficiency of supply management.

#### CompactFlash\* card

The CompactFlash\* card offers abundant storage spaces for typefaces, logos, standard forms and signatures as well as individual API or PRESCRIBE macros.

#### Warranty

2 year warranty as standard. Kyocera Mita guarantees the drum and developer for 3 years or 100,000 pages (whichever occurs sooner), provided each printer is used and cleaned in accordance with the service instructions.

**KYOlife** The up to 5 years on-site warranty extension for printer and options.

Your authorised Kyocera Mita distributor:



Kyocera Mita Europe, Hoeksteen 40, 2132 MS Hoofddorp, The Netherlands  
Tel +31 (0) 20 65 40 000, Fax +31 (0) 20 65 31 256, www.kyoceramita-europe.com