

ViewSonic®

VE150m LCD Display

ViewPanel® Series



15" TFT Multimedia LCD Colour Display

The VE150m multimedia ViewPanel produces sharp, crisp text and images with a high contrast ratio of 300:1 and no screen flicker. The first 15" flat-panel LCD display to offer a fully automatic, zero-touch, auto-tune feature, the VE150m self corrects for video card anomalies like drift and non-VESA video timing, delivering the best possible image in all environments. At only 1.9-inches thin, this display is perfect for government, estate agents or medical offices and financial industries where space is at a premium. And the built-in speakers sound great, even when the display is wall mounted. The ViewSonic VE150m ViewPanel is a solid choice for users who want a lightweight, reliable, value-priced LCD display.

- Full 15.0" viewable screen
- 1024 x 768 true resolution
- OnView® controls including ViewMatch®
All screen adjustments are made via an on-screen menu using simple controls. ViewMatch allows the users to adjust the colour temperature and individual colour intensity for screen-to-print matching.
- Very high brightness – 250nits
- Very high contrast – 300:1
- ø-Touch™ auto tune
Automatically provides the best image by monitoring the signals from the computer and optimising the monitor settings.
- Slim 1.9" profile (panel only)
- Bezel-integrated speakers
- Anti-reflective coating
Minimises glare and reflections, reducing eyestrain and allowing for optimal viewing comfort.
- OSD Key lock and power lock
The key lock function locks the menu settings to protect from accidental or unwanted changes. The power lock prevents the monitor from being inadvertently switched off.



ViewSonic®
See the difference.®

www.ViewSonicEurope.com

ViewSonic®

VE150m LCD Display



15.0" TFT MULTIMEDIA DISPLAY

VIEWPANEL	Type Display Area Contrast Ratio Viewing Angle Light Source Response Time Brightness Glass Surface	TFT active matrix (16.7 million colours) 15.0" viewable 300:1 (typical) 120° horizontal, 100° vertical (typical @ 10:1 CR) Long life, 50,000 hrs. (min) 30ms (typical) 250 cd/m ² (typical) Anti-glare coat
ANALOG INPUT	Video Frequency Sync	RGB Analogue (75 ohms, 0.7/1.0 Vp-p) F _H :30-60kHz, F _V :50-75Hz H/V Separated (TTL)
COMPATIBILITY	PC Mac**	PC compatibles from VGA up to 1024x768 non interlaced Power Mac™ (up to 1024 x 768)
CONNECTORS	Analog RGB Power Audio Input	15-pin mini D-sub (attached) DC IN into head Stereo mini jack
AUDIO	Speaker Amplifier	Two 1.5W speakers 1.5W at 1kHz for THD 1%
POWER	Voltage Consumption	AC 100-240V (Universal) via external DC converter brick 30W (max)
CONTROLS	Physical OSD	Menu, down, up, select Contrast, brightness, auto adjust, H/V-position, H/V-size, fine tune, sharpness, ViewMatch® colour, ViewMeter®, OSD language, OSD position, OSD time out, resolution notice, volume, mute, recall
OPERATING CONDITION	Temperature	0°C to 40°C (32°F to 104°F) 10%-90% (no condensation)
DISPLAY AREA		304mm (H) x 228mm (V)
DIMENSIONS	Physical	374mm (W) x 351mm (H) x 135mm (D) 14.9" (W) x 13.8" (H) x 5.4" (D)
WEIGHT	Net	4.5 kg (9.9 lbs.)
OTHER		DDC1 & DDC2B
REGULATIONS		TCO '99 (black version: TCO '95), TÜV/GS, TÜV/ERGO, ISO 9241-3, ISO 9241-8, ISO 13406-2 (class 2), Energy 2000, CE, CB, FCC-B, UL, CSA, NEMKO, SEMKO, DEMKO, FIMKO, PCBC (B-Mark), PSB (S-Mark), C-Tick, GOST-R (PCT BZ02), IC-B, NOM, EPA, EMI/B, PC '99
POWER MANAGEMENT		Meets ENERGY STAR®, VESA® DPMS, Energy 2000 standards
WARRANTY		Three-year limited warranty on parts, labour and backlight.

• ViewSonic Wizard

The ViewSonic Wizard software provides user-friendly installation. The enclosed CD-ROM automates the setup process to deliver optimised screen performance.

• TCO '99 and Energy 2000 certified**

This Monitor complies with the world's strictest standards for low emissions, safety, ergonomics, recycling and power management while saving costs through automatic power saving modes.



• PC & Mac® compatible*

• Kensington® security port

Kensington security port protects your assets.

• Three-year limited warranty

• VESA-compliant 75mm wall mount (optional)

The ViewSonic Universal Wall Mount provides full ViewPanel tilt, side-to-side tilt and portrait/landscape rotation, adding ergonomic adjustability and space savings.



ViewSonic®
See the difference.®

www.ViewSonicEurope.com

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Sweden
Finlandsgatan 18
164 74 Kista
Sweden

Tel: +46 (0) 8 507 13000
Fax: +46 (0) 8 507 13030

ViewSonic Finland
Lars Sonckin kaari 14
02600 Espoo
Finland

Tel: +358 (9) 5406 4070
Fax: +358 (9) 5406 4075

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

*May require optional Mac adapter. **Black Version: TCO '95.

Copyright © 2001, ViewSonic Corporation. All rights reserved. Corporate names and trademarks stated herein are the property of their respective companies. Specifications subject to change without notice. The EPA only promotes energy efficiency and does not endorse any particular company or product. VE 150m 06/01-UK