



hp LaserJet 4100

hp LaserJet 4100/n/tn/dtn

Superior HP LaserJet performance for better business results – the HP LaserJet 4100 is the most advanced workgroup printer yet, offering business users a reliable, easy to use and expandable platform to support printing e-services.

For business users in workgroup environments the HP LaserJet 4100 offers consistently high performance, enhanced printer management and e-service capabilities, as well as unrivalled expandability.

- Communicate more efficiently with high quality output of true 1200 x 1200 dpi at full 24 pages per minute engine speed without compromising performance.
- Experience enhanced printer management and maintenance with HP Web Jetadmin, an Embedded Web Server (set up configurable alerts via e-mail, change printer settings remotely, order consumables or link to on-line support).
- Implement new printing e-services with the ability to run downloadable Java based programmes using the Embedded Virtual Machine.

Setting a new performance standard for the workgroup.

- Save time and improve productivity with 24 pages per minute printing speed.
- Print complex documents that much faster, with a quicker return to the application with a new fast 250 MHz processor and standard memory of 16 MB RAM (32 MB on N/TN/DTN bundles, expandable up to 256 MB).
- Assured reliable performance in very busy office environments from up to 150,000 pages per month duty cycle.
- HP Supportpack included package extends the standard 1-year warranty to 3 years next day on-site warranty.

Make life easier with the HP LaserJet 4100, the intelligent printer geared to meet a workgroup's complex demands simply.

- Effortless printer management with HP Web Jetadmin allowing easy network installation, remote diagnostics and error correction.
- An Embedded Web Server (EWS) enables the HP LaserJet 4100 to communicate with users or administrators via standard web browser.
- New HP smart print supplies system allows you to view toner and media levels, tracks and collects and gives you the ability to order supplies via the web.* New 'no shake' toner cartridge delivers consistent, high quality results throughout its lifespan.

More versatile solutions for workgroup printing.

- Improve efficiency and meet the needs of global business with a variety of paper handling solution including paper input capacity of maximum 1600 sheets (up to three 500-sheet trays), optional duplex unit (standard for HP LaserJet 4100DTN) and an envelope feeder.
- HP's accessible architecture with Enhanced IO (EIO) interface, offers flexible connectivity via HP Jetdirect print servers and dozens of partner solutions for virtually all network environments.
- Simplify workflow and improve productivity with enhanced document management features like proof and hold, private printing, quick copy and booklet printing.



hp LaserJet 4100/n



hp LaserJet 4100tn/dtn







technical specifications

speed & throughput	24 ppm for A4 documents (12 ppm duplex speed). 250 MHz RISC microprocessor, instant-on fuser provides first page out in less than 12 sec from warm or cold start, HP Transmit Once for reduced network traffic, Maser (RIP once) in RAM enables MOPying from multiple original prints, (16 MB minimum)
print quality	HP Prores 1200 (true 1200 x 1200 dpi at 24 ppm), HP Fastres 1200 default setting (1200 dpi -like quality at 24 ppm), 600 dpi, economode with good print quality and 50% savings over regular dpi selections
standard software	Unattended software installation. HP internet installer can automatically update printer drivers during installation. HP Web Jetadmin printer management software for simple installation, configuration and management from a common web browser. Drivers in box: Microsoft* Windows* NT 4.0, 3.x, 9x, 2000, Me, Macinlosh* System 7.5.3 and above, AutoCAD Rel. 12/13/14. Drivers on the web: Windows NT 3.5.1, IBM* OS/2 Warp and Unix (HP-UX, Solaris, SunOS), IJNUX. Download available at http://www.hp.com. Printing from MS-DOS based applications in compatible mode.
paper handling	All HP LaserJet 4100 series: up to 4 input bins, 1600 sheets maximum input capacity (1 x 100 multipurpose, 3 x 500-sheet trays), HP LaserJet 4100TN/DTN: 500 sheet standard input capacity (1 x 100 multipurpose, 1 x 500-sheet trays), HP LaserJet 4100TN/DTN: 1100 sheets standard (1 x 100 multipurpose, 2 x 500-sheet trays). Multipurpose tray: Tray 1 (100 sheet/10 envelope) is used for automatic and manual feeding of envelopes, labels, transparencies, special media, 76 x 127 mm to legal (216 x 356 mm). 500-sheet input trays: Trays 2 and 3 (depending on the model) support A4, Letter, Executive, A5, B5, Legal and custom sizes. Standard output capacity of 300 sheets (250 sheets facedown, 50 face up) with output full sensor. Straight-through paper path, paper level indicators, optional autoduplex unit for two sided printing (standard in HP LaserJet 4100DTN), optional 75-sheet envelope feeder. Automatic duplex: supports A4, Letter, Legal, Executive, B5 paper sizes.
media types & weights	Paper: A4: 210 x 297 mm, A5: 148 x 210 mm, Letter: 216 x 279 mm, Legal: 216 x 356mm, Executive: 184 x 267 mm, Executive JIS minimum size: 76 x 127 mm, maximum size: 216 x 356 mm Envelopes: No. 10 Regular: 241 x 105 mm, Monarch: 98 x 190 mm, DL: 220 x 110 mm (print area), C5: 229 x 162 mm, B5: 250 x 176 mm Copier, bond, special application and recycled papers (overhead transparencies and labels designed for laser printer use Tray 1); Tray 1 handles 60 to 198 g/m² stocks, transparencies and labels: Tray 2/3, optional 500-sheet tray, automatic duplex unit handles 60 to 105 g/m² stock; envelope feeder and Tray 1 handles 75 to 105 g/m² envelopes
network connectivity	Bidirectional IEEE 1284-compliant parallel interface, two open EIO expansion slots for optional HP Jetdirect 610N (EIO) internal print servers for Ethernet 10Base-1, 10Base2, 100Base-1X, LocalTalk and Token Ring networks, Fast InfraRed port for optional InfraRed receiver, HP LaserJet 4100N/TND/TN printers, HP Jetdirect 610N (EIO) internal print server for Ethernet 10/100Base-TX Fast Ethernet network environments, Fast InfraRed port and receiver (optional), bidirectional IEEE 1284-compliant parallel interface, one open EIO expansion slot for optional HP and third-party accessories, HP Jetsend enabled, automatic switching between languages and ports, HP Web Jetadmin requires installation on one of the following network servers: Microsoft Windows NT, IBM OS/2 Warp, HP-UX or Solaris, HP Jetdirect 610N (EIO) internal print servers support all major network operating systems and provide flash memory for future upgrades
memory	HP LaserJet 4100:16 MB RAM, 3 expansion slots for additional memory expansion up to 256 MB HP LaserJet 4100N/TN/DTN: 32 MB RAM, 3 expansion slots for additional memory expansion up to 256 MB All HP LaserJet 4100 series printers: upgradeable to 256 MB of SDRAM memory, optional 5 GB HP EIO disk drive for mopying, forms, fonts, signatures, and job retention features
printer languages	HP PCL 6, HP PCL 5e, Postscript Level 3 emulation, automatic language switching
control panel	Intuitive operation and complete, easy to understand messaging, expanded control panel help for context-based problem resolution, two-line backlit LCD display and three LEDs. Messages can be displayed in 17 languages
typefaces	110 scalable True Type fonts (80 built-in, 30 via HP Fontsmart for Windows), all PCL and Postscript accessible
operating & environmental ranges	Temperature: operating 10 to 35° C, storage 0 to 35° C, Humidity: operating 20% to 80% RH, Storage 10% to 95% RH, Acoustics: operating position L+54 dB (A) printing, L<36 dB (A) standby (per ISO 9296, DIN 45635, T.19), bystander: 1m L<50 dB (A) Printing, L<30 dB (A) Standby (per ISO 7779, DIN 45635, T.19). Sound power: 0 Bels inaudible (A) Powersave L _{WMd} , 6.6 Bels (A) printing at 25 ppm L _{WMd} , 6.2 Bels (A) printing at 12 ppm L _{WMd}
power requirements	Source: 100 to 127 V (+/- 10%), 50/60 Hz (+/-2 Hz) or 220 to 240 V (+/-10%) 50/60 Hz (+/-2 Hz), printers voltage ranges depend upon the country in which the printer is purchased. Frequency: 50/60 Hz (+/- 2 Hz). HP Laserlet 4100 printers: printing: 317 W, standby: 21 W, Powersave: 16 W (EPA ENERGY STAR). HP Laserlet 4100N/TN/DTN printers: Printing: 385 W, Standby: 26 W, Powersave: 19 W EPA ENERGY STAR
size/weights	W x D x H: HP LaserJet 4100/N: 390 x 506 x 345 mm. HP LaserJet 4100TN: 390 x 506 x 465 mm. HP LaserJet 4100TN: 390 x 565 x 465 mm. Weight: HP LaserJet 4100/N: 18 kg. HP LaserJet 4100TN: 25 kg. HP LaserJet 4100TN: 28 kg
certifications	UL 1950/CSA 950 certified, complies with IEC 950/EN 60950, FCC Class B certified, CISPR-22 Level B, product CDRH certified Class 1 Laser Product (safe for office/EDP use). TÜV-GS approved. EPA ENERGY STAR Compliant. Blue Angel Certified
duty cycle	150,000 pages per month
warranty	Standard one year return to HP; HP Supportpack bundles come with a three year next day on-site warranty extension

*The HP smart print supplies system will not be available in all countries. For further information please contact your local dealer.

**Available in UK, Germany, France, Italy, Spain, Netherlands, Belgium, Austria, Portugal.

The HP LaserJet 4100 is available as part of HP Printadvantage, a complete package that lets you procure and manage your printing requirements in one easy transaction. For more information contact: http://www.hp.com/printadvantage HP has designated the HP LaserJet 4100/N/TN/DTN and their supplies for optimum print quality. For more information contact the Hewlett-Packard Internet website at: http://www.hp.com

For information on Third Party printing solutions please refer to http://www.jetcaps.com

For more information, please call your local HP sales office or representative: Austria: 0810/006080 (local rate call), Azerbaijan: (+994) 12 97 35 61, For more information, please call your local HP sales office or representative: Austria: 0810/006080 (local rate call), Azerbaijan: (+994) 12 97 35 61, Belgium and Luxembourg: (02) 778 34 00, Bulgaria: (+359) 2960 1940, CIS: (007) 095 797 3500, Croatia and Slovenia: (+385) 1) 60 60 200, Czech Republic: (00 420 2) 613 07 111 (Prague), Denmark: 45991125, Dubai (Gulf Region): (971) 488 15 456, East Central Europe (Vienna HQ plus Albania): (+43) 1-250 00, Finland: (09) 88721, France: (1) 69 82 6060, Germany: 0180 532 6222 (0.48 DM per minute), Greece: (01) 619 64 11, Hungary: (+36) 1 382-1111, Iceland: (354) 570 1000, Ireland: (00) 353 1 61 58 200, Israel: (972) 9 952 4848, Italy: (02) 92121, Kasachstan: (+7) 3272 98 08 24, Morocco (African Region): (212) 222 21340, Netherlands: (020) 5476666, Norway: 22 735600, Poland: (22) 865 98 00, Portugal: (808) 206 001, Romania: (+401) 250 6197, RSA: (27)11 806 1000 Slovakia: (+421 7) 68 20 90 11, Spain: (91) 6311600, Sweden: (08) 444 2000, Switzerland: 0848 88 44 66, Turkey: (0212) 2216969, UK: (0990) 474747, Ukraine: (+380) 44 490 6120, Uzbekistan: (+998) 71 169 1488, Yugoslavia: (+381) 11 627 134, Multi Country Operations (MCO) (Geneva): (22) 7804111, European Headquarters (Geneva): (22) 7808111.

ordering information

C8049A	hp LaserJet 4100
C8050A	hp LaserJet 4100n
C8051A	hp LaserJet 4100tn
C8052A	hp LaserJet 4100dtn
C9164A	hp LaserJet 4100 including supportpack**
C9165A	hp LaserJet 4100n
	including supportpack**
C9166A	hp LaserJet 4100tn
C9167A	including supportpack**
C916/A	hp LaserJet 4100dtn including supportpack**
	supplies & accessories
C8053A	75-sheet envelope feeder
C8054A	automatic duplex unit
C8055A	500-sheet optional
2005/8	paper feeder and tray
C8056A	500-sheet universal replacement tray (x, y adjustable)
C8061X	hp ultraprecise toner
	cartridge (10,000 pages)
C8061A	hp ultraprecise toner cartridge (6,000 pages)
C4103A	fast infrared receiver
J6054A	hp EIO disk drive – 5 GB
	memory & cables
C7842A	8 MB SDRAM DIMM
C7843A	16 MB SDRAM DIMM
C7845A	32 MB SDRAM DIMM
C7846A	64 MB SDRAM DIMM
C9121A	128 MB SDRAM DIMM
C2950A	IEEE 1284-compliant parallel printer cable, 2 metre
C2951A	IEEE 1284-compliant parallel
	printer cable, 3 metre
922158	macintosh serial cable
	hn istdirect 600n/610n
	hp jetdirect 600n/610n internal print servers
J3110A	Ethernet (10Base-T)
J3111A	Ethernet (10Base-T,
	10Base2) and LocalTalk
J4167A	Token Ring

printer connectivity solutions hp jetdirect connectivity card J4135A for USB, serial, and

Fast Ethernet (100Base-TX) and Ethernet (10Base-T) (included with hp LaserJet 4100n/tn/dtn models)

LocalTalk connections

J4169A

service & support H5479A hp supportpack – next business day, on-site response, 3 years C8057A maintenance kit 110v, 200,000 pages C8058A maintenance kit 220v, 200,000 pages

Microsoft, Windows and MS Windows are U.S. registered trademarks of Microsoft Corporation. All other brands and product names are trademarks or registered trademarks of their respective companies. The information in this document is subject to change without notice.

© Copyright Hewlett-Packard 2001 Printed in the Netherlands 02/01 5980-4366EEE